

TOBY-L100


LTE module

Standard Professional Automotive

CELLULAR

Highlights

- Single-mode LTE LGA module in a very small form-factor
- LTE Cat. 3, 100 Mb/s download, 50 MB/s upload
- Easy migration from u-blox W-CDMA, CDMA, GSM modules
- North American region (Verizon)
- Industrial temperature range: -40 to +85°C
- Manufactured in ISO/TS 16949 certified production sites



TOBY-L100:
24.8 x 35.6 x 2.6 mm

Product description

The TOBY-L100 single-mode LTE module in a very small form-factor is easy to integrate in compact designs. The TOBY-L100 supports up to two LTE-FDD bands. As a single-mode LTE module, it offers cost advantages compared to multi-mode (LTE/3G/2G) modules, and is optimized for applications using only LTE networks.

The TOBY-L100 module is dedicated to data transfer, supporting a high-speed USB 2.0 interface. With LTE Category 3 data rates of 100 Mb/s (downlink) and 50 Mb/s (uplink), the module is ideal for applications requiring the highest data-rates and high-speed internet access. It is the perfect choice for consumer fixed-wireless terminals, mobile routers and gateways, and applications requiring video streaming. It is also optimally suited for industrial (M2M) applications, such as remote access to video cameras, digital signage, telehealth, security and surveillance systems.

The TOBY-L100 can operate in a temperature range of -40 to +85°C, making it well suited to devices intended for outdoor operation and harsh environments.

The compact LGA package enables easy manufacturing, and straightforward migration from u-blox GSM/GPRS, W-CDMA(UMTS) and CDMA modules. This allows customers to take maximum advantage of their hardware and software investments, and provides very short time-to-market. The module is fully certified for the Verizon network. USB drivers and RIL software for Android are available free of charge.

TOBY-L100 modules are manufactured in ISO/TS 16949 certified sites. Each module is tested and inspected during production.

Product selector

Model	Region	Access Technology	GNSS	Interfaces	Audio	Features	Grade
		3GPP Release Baseline LTE FDD Category LTE Bands MIMO	GNSS receiver	UART USB 2.0 RMII / RGMII SDIO (Master/Slave) GPIO	CSFB VoLTE	Antenna Supervisor Jamming Detection Embedded TCP/UDP Embedded HTTP, FTP, SSL AssistNow software CellLocate® FOTA FW update via serial eCall / ERA GLONASS	Standard Professional Automotive
TOBY-L100	N. America (Verizon)	9 3 4,13 2x2		• 6		• •	Professional

Features

LTE	Cat. 3 50 Mb/s UL, 100 Mb/s DL FDD Bands 4, 13 3GPP Release 9 FDD channel bandwidth 1.4 - 20 MHz MIMO 2x2 Rx diversity
SMS	SMS via embedded IMS ¹
Network	Status Indication via LED
Firmware upgrade	FOTA (Firmware upgrade Over The Air) ²

¹ IP Multimedia Subsystem

² Available in FW version 015

Electrical data

Power supply	3.4 V to 4.5 V
Power consumption	
Power Off	40 µA
Idle (power saving)	2.6 mA
Transmitting	740 mA (Band 4, 10 MHz channel width)
Transmitting	800 mA (Band 13, 10 MHz channel width)

Interfaces

Serial	1 USB 2.0 (high-speed, 480 Mb/s)
GPIO	6 GPIOs ²
(U)SIM	1 4-wire interface, Supports 1.8 V and 3 V, SIM toolkit

² Available in FW version 015

Package

152 pin LGA (Land Grid Array): 24.8 x 35.6 x 2.6 mm, < 7 g

Environmental data, quality & reliability

Operating temperature -40 to +85°C (extended range)
RoHS compliant (lead-free)
REACH compliant
Manufactured in ISO/TS 16949 certified production sites

Certifications and approvals

GCF, FCC, Verizon.
See the u-blox website for latest approvals.

Support products

EVK-L10	Evaluation kit for TOBY-L100
RIL software	Android 4.x
USB driver	Windows Vista, Windows 7 and 8

Product variants

TOBY-L100	LTE Cat 3, Bands 4,13 (Verizon)
-----------	---------------------------------

Legal Notice

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.

Copyright © 2015, u-blox AG

Further information

For contact information, see www.u-blox.com/contact-us.
For more product details and ordering information, see the product data sheet.